




研域
YENTEK

深圳市汉智星科技有限公司

ITX-Q85M1 VER:1.0A 规格表



ITX-Q85M1 VER:1.0A 正面图



ITX-Q85M1 VER:1.0A I/O 图



ITX-Q85M1 VER:1.0 侧面图



研域
YENTEK

深圳市汉智星科技有限公司

| | |
|----------------------------|---|
| Product model | ITX-Q85M1 VER:1.0A |
| processor | Supports LGA1150 Intel® Celeron/Pentium/Core™ i3/i5/i7 processors |
| chipset | Intel® Q85 high-speed chipset |
| Internal memory | 1* DDRIII DIMM memory slot, supporting a single channel of 1600/1333MHz memory, up to 8GB |
| display | Integrated Intel® HD graphics controller, supporting DirectX11.2,OpenGL4.3 |
| | 1*VGA,2*HD OUTPUT display output, support VGA/HD OUTPUT synchronous/asynchronous display |
| network | 2* WGI210AT Gigabit network adapter chip, support network wake up /PXE function |
| deposit | 2* SATA hard disk interface (where SATA1 supports SATA3.0, transmission speed up to 6Gbps) |
| | 1* MSATA slot, support SSD, support 4G module or Intel protocol SSD, transmission speed up to 6Gbps |
| | Note:MSATA supports TPM-4COM to expand four serial ports, requiring material changes and BIOS changes |
| Tone frequency | Onboard ALC888S 7.1+ 2-channel hi-Fi audio controller with MIC/Line-out support |
| Expansion slot | 1 x PCIE X16 slot |
| | 1* M.2 slot, supporting the M.2 Key E 2230 WIFI module |
| I/O ports on the backplane | 1* PS/2 interface (expandable keyboard and mouse) |
| | 1 x VGA display port |
| | 1* HD OUTPUT display interface |
| | 2* DB9 COM serial port, support 9pin live function, support RS485/422 |
| | 4* USB 2.0 port |

保存期限：三年

表单编码：QR-HZX-PD-004 (A0)



| | |
|------------------------|---|
| | 2* USB 3.0 interface |
| | 2* RJ-45 Gigabit network interface |
| | 1 * Dual-layer audio interface (sound output and MIC input) |
| Built-in I/O interface | 1* 20pin ATX power outlet, |
| | 1*4pin ATX power interface |
| | 1* PS/2 keyboard and mouse interface 1*6Pin |
| | 4 x RS232 serial port 2 x 20pin |
| | 1* front audio interface 2*5pin |
| | 1* HD OUTPUT port 2*8Pin |
| | 1*JVGA port 1*12pin, same signal as DB15 |
| | 4* USB 2.0 interface 2*5Pin |
| | 2* USB3.0 interface 2*10pin |
| | 1* SIM card slot |
| | 1* Front panel function button and indicator port 2*5pin |
| Fan interface | 1* 4pin CPU fan interface; 1* 4pin system fan port |
| BIOS | 64Mb Flash ROM |
| GPIO | Supports four input and output interfaces |
| Guard dog | Support hardware reset function (256 level, 0~255 seconds) |
| Operating system | Windows 7/Windows 10/Linux |
| Power supply type | Powered by ATX 24Pin and 4pin power supplies |
| Operating temperature | -10°C to 60°C |
| Storage temperature | -20°C to 70°C |
| Working humidity | 5%-95% relative humidity, no condensation |



研域
YENTEK

深圳市汉智星科技有限公司

| | |
|-----------|---------------|
| dimension | 170mm x 170mm |
|-----------|---------------|

订购信息:

| No. | Model | Processor | Chipset | Memory | VGA | HD OUTPUT | LAN | USB | COM | RS485/RS422 | Power |
|-----|-----------------------|-----------|---------|--------|-----|-----------|----------|-----|-----|-------------|-------|
| 1 | ITX-H81R1 VER:1.0A | LGA1150 | H81 | 1*DDR3 | 1 | 1 | 2*8111H | 10 | 6 | 2 | ATX |
| 2 | ITX-P85M1 VER:1.0 | LGA1150 | Q85 | 1*DDR3 | 1 | 1 | 2*210AT | 12 | 6 | 2 | ATX |
| 3 | ITX-Q85M1 VER:1.0A | LGA1150 | Q85 | 1*DDR3 | 1 | 1 | 2*1210AT | 12 | 6 | 2 | ATX |