


## STX-R19E VER1.0 规格表



STX-R19E VER:1.0 主板正面图



STX-R19E VER:1.0 主板正面 IO 图



STX-R19E VER:1.0 主板背面 IO 图



STX-R19E VER:1.0 主板侧面图

Product model	STX-R19E VER:1.0
processor	Integrated Intel® J1900/2.0GHz quad-core processor.TDP 10W
chipset	Based on Intel® Bay trail SOC platform
Internal memory	1*SO DDRIII slot, supporting only 1600/1333MHz DDR3L/1.35V memory, up to 8GB
display	Integrated Intel®HD Graphics core graphics card
	1 x VGA port
network	4* Intel WGI211AT Gigabit network adapter chip, supporting network wake up /PXE function
deposit	1* Standard SATA2.0 hard disk interface, transmission speed up to 3Gbps
Tone frequency	N/A
Expansion slot	1* MSATA slot, support SSD SSD,SSD transmission speed up to 3Gbps
	1 x Mini-PCIE slot, supporting 4G modules
I/O ports on the front panel	1* standard RS232 serial port
	2* USB 2.0 port
	1* USB 3.0 interface
	1* Power lamp
	1* hard disk indicator
	1* Power switch
	4* RJ-45 Gigabit network interface
	1 x VGA port
	1 x 12V DC power input port
Built-in I/O interface	1* PS/2 Mouse and keyboard interface 1*6Pin
	1* Front panel function button and indicator port 2*5pin
	1* hard disk power port 4 pins
	1* 4pin ATX power interface (12V input/output power interface)

Fan interface	Fan-less cooling design, reserved 1*3pin CPU intelligent fan interface
GPIO	Supports four input/output GPIO
BIOS	64Mb Flash ROM
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Operating system	Windows 7/Windows 10/Linux
Power supply type	Adopts DC 12V power supply
Operating temperature	-10℃ to 60℃
Storage temperature	-20℃ to 70℃
Working humidity	5%-95% relative humidity, no condensation
dimension	120mm x 120mm

## 订购信息:

No	Model	Processor	Frequency	Memory	VGA	LAN	USB2.0	USB3.0	COM	Power
1	ITX-R19E VER:1.0	J1900	2.0G	1*SODDDR3L	1	4* WGI211AT	2	1	1	DC12V